

Push Plates



30S | A30S

Square Corner - Beveled Push Plate

Certification: Meets ANSI A156.6 for J301 Push Plate
 Gauge: • 30S - 0.050" (1.3 mm)
 • A30S - 0.062" (1.6 mm)
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4 (30S only), US10 (A30S only), DBZ, US19, US26D (30S only), US28, US32, US32D
 Fasteners: Six (6) #6 x 5/8" OPH tapping screws
 Options: May be ordered cut for cylinder (CFC)

Available in Sizes					
Inches	3 x 12	3-1/2 x 15	4 x 16	6 x 16	8 x 16
Millimeters	76 x 305	89 x 38	102 x 406	152 x 406	203 x 406



40R | A40R

Radius Corner - Beveled Push Plate

Certification: Meets ANSI A156.6 for J301 Push Plate
 Gauge: • 40R - 0.050" (1.3 mm)
 • A40R - 0.062" (1.6 mm)
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4 (40R only), US10 (A40R only), DBZ, US19, US26D (40R only), US28, US32, US32D
 Fasteners: Six (6) #6 x 5/8" OPH tapping screws
 Options: May be ordered cut for cylinder (CFC)

Available in Sizes					
Inches	3 x 12	3-1/2 x 15	4 x 16	6 x 16	8 x 16
Millimeters	76 x 305	89 x 38	102 x 406	152 x 406	203 x 406



50T | A50T

Round Corner - Beveled Push Plate

Certification: Meets ANSI A156.6 for J301 Push Plate
 Gauge: • 50T - 0.050" (1.3 mm)
 • A50T - 0.062" (1.6 mm)
 Materials: Aluminum, brass, bronze, stainless steel
 Finishes: US3, US4 (50T only), US10 (A50T only), DBZ, US19, US26D (50T only), US28, US32, US32D
 Fasteners: Six (6) #6 x 5/8" OPH tapping screws
 Options: May be ordered cut for cylinder (CFC)

Available in Sizes			
Inches	3 x 12	3-1/2 x 15	4 x 16
Millimeters	76 x 305	89 x 38	102 x 406