

## 3840S - PRIVACY - F22

3840S



### SPECIFICATIONS

<b>Applications</b>	<ul style="list-style-type: none"><li>• Heavy Duty Commercial</li><li>• Industrial</li><li>• Institutional</li></ul>
<b>Backsets</b>	2-3/4" (70mm)
<b>Certifications</b>	<ul style="list-style-type: none"><li>• ADA Compliant ANSI A117.1 Accessibility Code</li><li>• UL/cUL Listed for all functions up to 3 hours "A" label single doors</li><li>• UL10C Positive Pressure Rated</li><li>• BHMA Certified ANSI A156.13, Series 1000, Grade 1</li></ul>
<b>CTC Length</b>	3-5/8" (92mm)
<b>Door Thickness</b>	1-3/4" - 2" (45 mm - 51 mm) Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep
<b>Exposed Trim</b>	<ul style="list-style-type: none"><li>• Cast Zinc - Standard</li><li>• Cast Stainless Steel - Optional for Withnell (WTS) and William (WLS) only</li></ul>
<b>Finishes</b>	<ul style="list-style-type: none"><li>• US3, US4, US10B, US26, US26D, US32D*</li><li>• *US32D look on a cast zinc lever</li><li>• Withnell or William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order</li><li>• US3, US4 and US26 subject to extended lead time</li></ul>
<b>Functions</b>	Privacy (F22)
<b>Latchbolt Type</b>	3/4" (19 mm) throw with anti-friction tongue, all stainless steel
<b>Lever Options</b>	Archer, August, Charles, Johnston, Joshua, Louis, Warren, William and Withnell
<b>Lock Chassis</b>	4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)
<b>Notes</b>	<ul style="list-style-type: none"><li>• Emergency release on exterior side via supplied key</li><li>• No exposed mounting screws</li><li>• Concealed thru-bolts</li><li>• Body is easily field reversible (shipped LHR by default)</li><li>• Self adjusting case for beveled doors</li></ul>
<b>Options</b>	<ul style="list-style-type: none"><li>• Tactile Warning</li><li>• Lead Lining</li></ul>

- Split Finish
- Factory Handing Available (if specified)
- ADA Thumbturn

**Rose Diameter**

2-7/16" (62mm)

**Strikes**

- 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike
- Optional strikes available

**Warranty**

Lifetime