LATCH-GARD_®



Latch-Gard products are made in the U.S.A. using high quality materials. Our security plates are available in three colors and many different styles for your various applications.

PROTECT

PREVENT

Against Break-ins

Expensive Repairs

The LG100/LG110 Series latch protectors are manufactured using heavy 12 gauge plate steel for maximum security.

All Latch-Gard models are available with Special Fasteners which allow for a quick and easy, flush inside installation.

Latch-Gard steel plates completely cover the latch area protecting the latch bolt while a jamb-pin prevents prying door open.

Easy installation requires drilling only three holes.

Reversible for right or left openings.

Item Description

For Mortise Locksets: LG100Z (3" x 11") Latch-Gard with jamb pin and hex nuts-zinc plated. LG100Z/SF (3" x 11") Latch-Gard with jamb pin and SF710 fasteners-zinc plated. LG100Z/SFNP (3" x 11") Latch-Gard no jamb pin and SF710 fasteners-zinc plated. (3" x 11") Latch-Gard with jamb pin and SF710 fasteners-duronodic. LG100D (3" x 11") Latch-Gard no jamb pin and SF710 fasteners-duronodic LG100DNP (3" x 11") Latch-Gard with jamb pin and SF710 fasteners-bright brass plated. LG100BB Cut-out models for Cylindrical Locksets: LG110Z (3" x 11") Latch-Gard with jamb pin and hex nuts-zinc plated. (3" x 11") Latch-Gard with jamb pin and SF710 fasteners-zinc plated. LG110Z/SF LG110Z/SFNP (3" x 11") Latch-Gard no jamb pin and SF710 fasteners-zinc plated. (3" x 11") Latch-Gard with jamb pin and SF710 fasteners-duronodic. LG110D (3" x 11") Latch-Gard no jamb pin and SF710 fasteners-duronodic LG110DNP (3" x 11") Latch-Gard with jamb pin and SF710 fasteners-bright brass plated. LG110BB (3" x 11") Latch-Gard with pin double cut-out (5-1/2" centers) and SF710-zinc. LG20Z

Latch-Gard protectors are shrink-wrapped with a card for display. All products are available (bulk packed) without packaging.

LATCH-GARD_®

P.O. Box 425 Wakarusa, IN 46573-0425 574-862-2373 www.latchgard.com

SPECIFICATIONS

Plate: 12 gauge steel, .105" thick. Two square holes in plate. 5/8" in from top and bottom, and 5/8" in from side. Bolts: Two carriage bolts 5/16-18 x 2-1/4" long with hex nuts or 1-1/2" long with special fasteners. Pin, 1/2". Finish: Zinc plated with brushed finish, Duronodic powder painted, Bright Brass plated with brushed finish.





This narrow-short latch protector installs on all cylindrical locks, Type 161 plus Mono-Lock[®], Unilock[®] and Integralocks[®].

Includes special SF700 fasteners.

Available in Zinc, Duronodic and Bright Brass finishes.

LG130 Series (1-1/2" x 10")

This model installs on rose or escutcheon 3-1/2" or less. Also Type 86 mortise or Type 161 cylindrical locks.

Includes Special SF710 fasteners.

Available in Zinc, Duronodic and Bright Brass finishes.

LG140 Series (2-1/2" x 10")

Models install on rose or escutcheon 2-3/4" or less. Also provides security for electric strikes.

Includes special SF710 fasteners.

Available in Zinc, Duronodic and Bright Brass finishes.

Item	Description
LG120Z	(1-1/2" x 6") Latch-Gard narrow-short with SF700 fasteners-zinc plated.
LG120D	(1-1/2" x 6") Latch-Gard narrow-short with SF700 fasteners-duronodic.
LG120BB	(1-1/2" x 6") Latch-Gard narrow -short with SF700 fasteners-bright brass plated.
LG130Z	(1-1/2" x 10") Latch-Gard narrow with SF710 fasteners-zinc plated.
LG130D	(1-1/2" x 10") Latch-Gard narrow with SF710 fasteners-duronodic.
LG130BB	(1-1/2" x 10") Latch-Gard narrow with SF710 fasteners-bright brass plated.
LG140Z	(2-1/2" x 10") Latch-Gard with SF710 fasteners-zinc plated.
LG140D	(2-1/2" x 10") Latch-Gard with SF710 fasteners-duronodic.
LG140BB	(2-1/2" x 10") Latch-Gard with SF710 fasteners-bright brass plated.
	LG120Z LG120D LG120BB LG130Z LG130D LG130BB LG140Z LG140D

Latch-Gard latch protectors are poly-bagged with a card for display. All products are available (bulk packed) without packaging.

LATCH-GARD_®

SPECIFICATIONS

P.O. Box 425 Wakarusa, IN 46573-0425 574-862-2373 www.latchgard.com

Plate: 12 gauge steel, .105" thick. Two square holes in plate
Bolts: Two carriage bolts 5/16-18 x 1-1/2" long with special fasteners. (1/4-20 bolts with LG120)
Finish: Zinc plated with brushed finish, Duronodic powder painted, Bright Brass plated with brushed finish.

LATCH-GARD.

PROTECT Against Break-ins

PREVENT **Expensive Repairs**





LG150 Series (2-5/8" x 6")

Models install on doors with cylindrical locks and narrow door frames.

Includes Special SF710 fasteners.

Available in Zinc, Duronodic and Bright Brass finishes.

LG160 Series (2-5/8" x 12")

Models fit Adams-Rite Locks.

Installs on aluminum entrance doors. 1-1/2" cylinder hole fits over lock.

Includes Special SF710 fasteners.

Available in Zinc, Duronodic and Bright Brass finishes.

Item LG150Z LG150D LG150BB LG160Z LG160D

Description

(2-5/8" x 6") Latch Gard with SF710 fasteners-zinc plated. (2-5/8" x 6") Latch Gard with SF710 fasteners-duronodic. (2-5/8" x 6") Latch Gard with SF710 fasteners-bright brass plated. (2-5/8" x 12") Latch Gard with SF710 fasteners-zinc plated. (2-5/8" x 12") Latch Gard with SF710 fasteners-duronodic. **LG160BB** (2-5/8" x 12") Latch Gard with SF710 fasteners-bright brass plated.

Latch-Gard protectors are poly-bagged with a card for display. All products are available (bulk packed) without packaging.

ATCH-GARD P.O. Box 425

Wakarusa, IN 46573-0425 574-862-2373 www.latchgard.com

SPECIFICATIONS

Plate: 12 gauge steel, .105" thick. Two square holes in plate

Bolts: Two carriage bolts 5/16-18 x 1-1/2" long with special fasteners.

Finish: Zinc plated with brushed finish, Duronodic powder painted, Bright Brass plated with brushed finish.

LATCH-GARD.

PROTECT Against Break-ins

PREVENT

Expensive Repairs





LG151 Series (4" x 6")

Models install on many modular office doors with aluminum frame.

Offset can be used to overlap frame preventing door-jamb separation.

Includes Special SF710 fasteners for use with either 1-1/2" or 1-1/4" carriage bolts.

LG110 Series (3" x 11")

Models fit many modular office doors with steel or aluminum frame.

Universal installation works on many doors.

Includes Special SF710 fasteners.

Available in Zinc, Duronodic finishes only.

ltem LG151Z

LG110Z/SFNP

LG100Z/SFNP

Description

(4" x 6") Latch-Gard with SF710 fasteners-zinc plated.
(3" x 11") Latch-Gard no pin with SF710 fasteners-zinc plated.
(cut-out model)
(3" x 11") Latch-Gard no pin with SF710 fasteners-zinc plated.

Latch-Gard protectors are shrink wrapped with a card for display. All products are available (bulk packed) without packaging.

LATCH-GARD.

P.O. Box 425 Wakarusa, IN 46573-0425 574-862-2373 www.latchgard.com

SPECIFICATIONS

 Plate:
 12 gauge steel, .105" thick. Two square holes in plate

 Bolts:
 Two carriage bolts 5/16-18 x 1 1/2" long with special fasteners.

 Finish:
 Zinc plated with brushed finish, Duronodic powder painted, Bright Brass plated with brushed finish.



PROTECT Against Break-ins

PREVENT Expensive Repairs

LG170-171 Series (1-7/8" x 14")This model installs on office or wood trim doors needing a larger offset.The LG170 provides for a 3/8" offset while the LG171 offers a 1/2" offset.Latch-Gard products are made in the U.S.A. using high quality materials. Our security plates are available in three colors and different styles for your various applications.Both the LG170 and LG171 come with SF700 fasteners for a smooth look both inside and outside the door.Reversible for right or left openings.

Item Description

the log of the second se		
LG170Z	(1-7/8" x 14") Latch-Gard with 3/8" offset and SF700 fasteners-zinc plated.	
LG170D	(1-7/8" x 14") Latch-Gard with 3/8" offset and SF700 fasteners-duronodic.	
LG170BB	(1-7/8" x 14") Latch-Gard with 3/8" offset and SF700 fasteners-bright brass plated.	
LG171Z	(1-7/8" x 14") Latch-Gard with 1/2" offset and SF700 fasteners-zinc plated.	
LG171D	(1-7/8" x 14") Latch-Gard with 1/2" offset and SF700 fasteners-duronodic.	
LG171BB	(1-7/8" x 14") Latch-Gard with 1/2" offset and SF700 fasteners-bright brass plated.	

Latch-Gard latch protectors are poly bagged with a card for display. All products are available (bulk packed) without packaging.

LATCH-GARD® P.O. Box 425

P.O. Box 425 Wakarusa, IN 46573-0425 574-862-2373 www.latchgard.com

SPECIFICATIONS

Plate: Heavy 16 gauge steel. Two square holes in plate. 3/8" offset (LG170) or 1/2" offset (LG171)
Bolts: Two carriage bolts 1/4-20 x 1-1/2" long with SF700 fasteners.
Finish: Zinc plated with brushed finish, Duronodic powder painted, Bright Brass plated with brushed finish.