

HG315 Edge Mount Hinge Guard

Standard Features

Barrel Type Hinge

.187" diameter stainless steel pin (rod)
Flanged nylon bearings
Stainless steel end pins

Material

Heavy-duty 14 gauge stainless steel

Finishes

US32D Satin Stainless Steel (630)

Standards

ANSI/BHMA Standard A156.26
Grade 1

Mounting Hardware

Fasteners concealed when door is closed
Universal screw pack provided

Capacity

Supports weights up to 600lbs.
4'0" maximum door width

Standard Sizes

6'8", 7'0", 7'2", 8'0", 10'0"

Hole Pattern

Symmetrically templated

Handing

Not required for standard 7'0", 8'0" or 10'0". Specify handing for 6'8" and 7'2" and for most optional features

Fire Rating

3 hours- hollow metal doors
90 minutes- hollow metal and composite core wood fire doors
20 minutes- wood doors



Classified in accordance with UL10C for positive pressure



Fire-rated label

Optional Features

Finishes

US32 Bright Stainless Steel (629)
Scratch-Resistant Powder Coated Paint

Other Features

Custom lengths- specify in inches
Custom hole pattern
Dutch door hinges- suffix "DDP"
Hospital tips – suffix "HT"
Raised barrel - suffix "RB"
Special sheared leaf

Fasteners

Tamper-proof security screws

Electrical Modifications

Current Transfer Prep - suffix "CTP"
Adjustable Monitoring Switch - suffix "AMS"
Electrical Transfer Access Prep - suffix "ETAP"

ElectroLynx™

EL4 (4 wire), EL8 (8 wire), EL12 (12 wire)

Featuring our unique edge guard, this economical hinge prevents objects from being placed between the door and frame as well as protects the door's edge while supporting the door's weight along the entire length of the jamb.

