



110S

Silicone Closed Cell Sponge Seal

PRODUCT CUT SHEET

PROJECT:

SUBMITTED BY:

DATE:

NOTES:


Material

Aluminum Alloy 6063, T5 Temper
Synthetic Rubber Polymer: Closed Cell Sponge
Silicone Sponge is Black

- Excellent Flexibility and Memory
- Flame-Resistant
- Moisture-Resistant
- Temperature Range -81°F to 300°F, Remains Flexible at Extreme Temperatures
- Excellent Resistance to Ozone, UV and Aging
- Recommended for Areas Using FM200 or Halon Fire Suppression Systems
- BHMA Certified to ANSI/BHMA A156.22 Performance Tests for Heat and Cold
- #6 x 3/4" Stainless Steel Sheet Metal Screws Furnished
- Screw Holes Slotted for Adjustment
- Patent Pending Microcellular Silicone

Finishes

110SA Anodized Aluminum
110SB Black Anodized
110SDKB Dark Bronze



NGP-GKT-110S-PCS-0626-A

NATIONAL GUARD PRODUCTS, INC.

MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706

Fax: (800) 255-7874
Email: info@ngp.com

Quotes: quotes@ngp.com
Orders: orders@ngp.com

ngp.com
1-800-NGP-RUSH