



225WHA

Nylon Brush Mortise Automatic Door Bottom

PRODUCT CUT SHEET

Material

Aluminum Alloy 6063, T6 Temper
Synthetic Polymer: Polyamide
Nylon Brush is Black

- BHMA Certified to ANSI/BHMA A156.22, 1,000,000 Cycle Test-Grade 1
- BHMA Certified to ANSI/BHMA A156.22 Performance Tests for Heat and Cold
- Excellent Abrasion Resistance, Flexibility and Memory
- Moisture-Resistant
- Retains Insecticides Well
- Temperature Range -70°F to 425°F
- REACH and RoHS Compliant
- Not Effective Against Water Penetration
- Use with a Threshold for Maximum Sealing Capability
- Nylon Brush Recommended for Carpet Applications Where No Threshold is Provided
- Specify Exact Net Length Required to Avoid Field Sizing
- Furnished ½" Shorter Than Ordered to Fit Within Net Door Size. (i.e. 36" is Furnished 35 ½")
- ADB's from 12" to 18" Can be Cut Down ½". ADB's 20" and Over Can be Cut Down up to 1 ½"
- Black Plastic End Caps Furnished Standard
- Available 11 ½" Net to 60" in Length
- Mortise Required 5/8" x 1 ½"
- ¾" Max Drop
- Non-Handed

Finish


Anodized Aluminum

Options

Lead Insert Available for Radiation Shield –
Specify 'Lead Lined'



PROJECT:
SUBMITTED BY:
DATE:
NOTES:



Provided Endcap

NGP-GKT-225WHA-PCS-0426-A

NATIONAL GUARD PRODUCTS, INC.

MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706

Fax: (800) 255-7874

Email: info@ngp.com

Quotes: quotes@ngp.com

Orders: orders@ngp.com

ngp.com
1-800-NGP-RUSH