



GAP90N

Gap Solution for Excessive Fire Door & Frame Clearances— 180 Minute PRODUCT CUT SHEET

**UL Certified for Head/Jamb Gaps —
Measuring Over 1/8", and up to 9/16"**



UL CERTIFIED FOR USE IN
THE US AND CANADA

- UL Certified Solution for Hollow Metal Fire Doors Rated up to 180 Minutes, and Wood Fire Doors Rated up to 90 Minutes with Excessive Clearance Between Door and Frame Over 1/8", up to 9/16" and a Soffit Measuring 1/2" to 1 3/8"
- Restricts the Passage of Smoke
- Non-Handed
- Available in 36", 48", 84" and 96" Lengths
- Multiple Strike Shims (9275 or 9225) may also be Required for Proper Latchbolt Engagement
- Doors with Parallel Arm Closers — Use 9990 Fire Door Top Gap Solution for Excessive Gaps up to 1/2"
- Patented: US Patent 9,273,510 B2

GAP90N


Requires Installation of ALL Components:
9945N, 9400GR, 5050C

GAP90NDBK

Requires Installation of ALL Components:
9945N, 9400C, 5050C

9945N

Steel Stop Extender



- 16-Gauge, Gray Primer Finish
- Furnished With #10 X 1" TEK SMS
- Patented: US Patent 9,273,510 B2
- Embossed with **UL Mark**

5050

Silicone Bulb Fire and Smoke Seal



9400

NGP-Edge® Intumescent Seal with PVC Cover

- Self-Adhesive



PROJECT:


SUBMITTED BY:

DATE:

NOTES:

INSTALLED VIEW

Alternate 5050
placement locations:



9945N

1/2" - 1 3/8"
SOFFIT DEPTH



1-9/16"

See Adhesive Specifications on Page G14

NGP-GAP-GAP90N-PCS-0526-A

NATIONAL GUARD PRODUCTS, INC.

MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706

Fax: (800) 255-7874

Email: info@ngp.com

Quotes: quotes@ngp.com

Orders: orders@ngp.com

ngp.com
1-800-NGP-RUSH