



# RO100

ADA Compliant Interlocking Offset Ramp  
18" Wide x 1/4" Tall With 1" Offset



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ Typical Wall Thickness: .110"
- ▶ 18" Wide x 1/4" Tall With 1" Offset
- ▶ Weight: 2.99 Lbs./Ft.
- ▶ BHMA Certified to ANSI/BHMA A156.21
- ▶ #10 FH Zinc Plated Wood Screws Included
- ▶ 1,000 Lb. Load Test



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1½ HOURS. CATEGORY J



[ngp.com](http://ngp.com)  
1-800-NGP-RUSH

FAX: (800) 255-7874  
QUOTES: [QUOTES@NGP.COM](mailto:QUOTES@NGP.COM)  
ORDERS: [ORDERS@NGP.COM](mailto:ORDERS@NGP.COM)

THRESHOLD

# INSTALLATION INSTRUCTIONS

1. Assemble ramp by interlocking sections together.
2. Cut ramp to fit.
3. Position return closed end (if ordered) on each side of ramp.
4. Drill and counter sink screw holes in ramp aligned with holes in RCE.
5. Install ramp with screws provided.
6. Caulk around base of ramp and RCE for moisture control.



THE PRODUCTS  
YOU COUNT ON  
THE PEOPLE  
YOU TRUST  
[ngp.com](http://ngp.com)

**NGP MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118

FAX: (800) 255-7874  
QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)  
ORDERS: [orders@ngp.com](mailto:orders@ngp.com)

**CARSON CITY**  
3689 Arrowhead Drive  
Carson City, NV 89706

