

# HP90

## HARDWARE PREP FILLERS



UL CERTIFIED FOR USE IN  
THE US AND CANADA

**UL Certified Solution for Fire Doors When Either Removing Existing Hardware and/or Using a New Hardware Type Over Existing Hardware Preps.**



- Application Certified on both Hollow Metal and Wood Fire-Rated Doors, up to 90 Minutes
- Certified for Use in Combination With Gap Guard Fire Caulk to Fill Thru-Holes Between ½" Diameter and 2 ½" Diameter



POSITIVE PRESSURE TESTED  
MISCELLANEOUS FIRE DOOR  
ACCESSORY

| PART NO.   | DESCRIPTION                                  |
|------------|----------------------------------------------|
| HP90 - 0.5 | ½" Diameter Hardware Prep Filler (10 Pack)   |
| HP90 - 1.0 | 1" Diameter Hardware Prep Filler (10 Pack)   |
| HP90 - 1.5 | 1 ½" Diameter Hardware Prep Filler (10 Pack) |
| HP90 - 2.0 | 2" Diameter Hardware Prep Filler (10 Pack)   |

# GAPGUARD FIRE CAULK



UL CERTIFIED FOR USE IN  
THE US AND CANADA

**UL Certified Solution for Fire Doors and Frames to Seal Thru-Holes as well as in Combination With Other Hardware Prep Filler Solutions.**

## PRODUCT INFORMATION

- Application Certified on Fire-Rated Hollow Metal Doors and Frames and Wood Doors
  - Can be Used to Fill up to a 1 ¾" Diameter Thru-Hole on up to 90-Minute Fire Doors and Frames
  - Can be Used to Fill Gap at the Bottom of Frame and Flooring, When Shimmed, up to ¾"
  - Can be Used to Fill the Gap Between the Door Frame Return, and the Wall, up to ¾"
  - Can be Sanded and Painted after Full Cure
  - Indoor Use Only
  - Shelf Life is 12 Months
  - 10.0 oz Cartridges, 10 per Box
  - 3.0 oz. Tubes, 6 per Box
- Color: Tan



POSITIVE PRESSURE TESTED  
MISCELLANEOUS FIRE DOOR  
ACCESSORY