



GAPGUARD FIRE CAULK

PRODUCT CUT SHEET

UL Certified Solution for Fire Doors and Frames to Seal Thru-Holes as well as in Combination With Other Hardware Prep Filler Solutions



- Application Certified on Fire-Rated Hollow Metal Doors and Frames and Wood Doors
- Can be Used to Fill up to a ½" Diameter Thru-Hole on 60- and 90-Minute Fire Doors and Frames
- Can be Used to Fill up to a 1" Diameter Thru-Hole on 20- and 45-Minute Fire Doors and Frames
- Can be Used to Fill Gaps up to ¾" Between Floor and Shimmed Frame Legs, Rated up to 90 Minutes
- Fully Cured in 24 Hours
- Can be Sanded and Painted after Full Cure
- Indoor Use Only
- Shelf Life is 12 Months
- 10.0 oz Cartridges, 10 per Box
- 3.0 oz. Tubes, 6 per Box

COLOR:

Tan

SPECIAL NOTES:

- 90-minute rated UL Certified Miscellaneous Fire Door Accessory on UL10B and UL10C wood or hollow metal fire doors
- Clean with soap and water before hardens
- Keep from freezing



PROJECT:

SUBMITTED BY:

DATE:

NOTES:

NATIONAL GUARD PRODUCTS, INC.

MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706

Fax: (800) 255-7874

Email: info@ngp.com

Quotes: quotes@ngp.com

Orders: orders@ngp.com

ngp.com
1-800-NGP-RUSH

NGP-GAP-FIRECAULK-PCS-0725-A