

HP90

HARDWARE PREP FILLERS



UL CERTIFIED FOR USE IN
THE US AND CANADA

UL Certified Solution for Fire Doors When Either Removing Existing Hardware and/or Using a New Hardware Type Over Existing Hardware Preps.



- Application Certified on both Hollow Metal and Wood Fire-Rated Doors, up to 90 Minutes
- Certified for Use in Combination With Gap Guard Fire Caulk to Fill Thru-Holes Between ½" Diameter and 2 ½" Diameter



POSITIVE PRESSURE TESTED
MISCELLANEOUS FIRE DOOR
ACCESSORY

PART NO.	DESCRIPTION
HP90 - 0.5	½" Diameter Hardware Prep Filler (10 Pack)
HP90 - 1.0	1" Diameter Hardware Prep Filler (10 Pack)
HP90 - 1.5	1 ½" Diameter Hardware Prep Filler (10 Pack)
HP90 - 2.0	2" Diameter Hardware Prep Filler (10 Pack)

GAPGUARD FIRE CAULK



UL CERTIFIED FOR USE IN
THE US AND CANADA

UL Certified Solution for Fire Doors and Frames to Seal Thru-Holes as well as in Combination With Other Hardware Prep Filler Solutions.

PRODUCT INFORMATION

- Application Certified on Fire-Rated Hollow Metal Doors and Frames and Wood Doors
 - Can be Used to Fill up to a 1 ¾" Diameter Thru-Hole on up to 90-Minute Fire Doors and Frames
 - Can be Used to Fill Gap at the Bottom of Frame and Flooring, When Shimmed, up to ¾"
 - Can be Used to Fill the Gap Between the Door Frame Return, and the Wall, up to ¾"
 - Can be Sanded and Painted after Full Cure
 - Indoor Use Only
 - Shelf Life is 12 Months
 - 10.0 oz Cartridges, 10 per Box
 - 3.0 oz. Tubes, 6 per Box
- Color: Tan



POSITIVE PRESSURE TESTED
MISCELLANEOUS FIRE DOOR
ACCESSORY