

HP90-FB

FLUSH BOLT HARDWARE PREP FILLER



UL CERTIFIED FOR USE IN
THE US AND CANADA



Filler Plate

HP90

GapGuard Fire Caulk Fill

HP90

Filler
Plate

**WOOD DOOR
INSTALLATION
SHOWN**

**UL Certified Solution for Fire Doors When
Either Removing Existing Hardware and/or
Using a New Hardware Type Over Existing
Hardware Preps.**

PRODUCT INFORMATION

- Application Certified On Both Hollow Metal And Wood Fire-Rated Doors Up To 90 Minutes
- Certified for Filling Manual or Automatic Flush Bolt Cavities
- Patented: US Patent US 11,959,332 B2

PRODUCT CONSISTS OF:

- + HP90 – 2"×6" Rectangular Fire-Rated Panel
- + HP90 – 0.5 Cylindrical Fire-Rated Panel
- + Steel Filler Plates: *(Powder Coated Primer Gray, Embossed With UL Mark)*
 - HP90-FBE6750, Edge Filler Plate
 - HP90-FBE8500, Edge Filler Plate
 - HP90-FBL2000, Latch Bolt Filler Plate
 - HP90-FBL2500, Latch Bolt Filler Plate
 - HP90-FBL3875, Latch Bolt Filler Plate
 - HP90-SF2250, Strike Filler Plate
- + Hardware Pack
 - #10-32×1-3/4" FHPH SS Machine Screw
 - #8×3/4" FHPH SS Combo Screw
 - #12×1" FHPH SS Combo Screw
 - #8×3/4" FHPH SS SMS
 - #12×1" FHPH SS SMS
- + GapGuard Fire Caulk
(see Installation Instructions)



POSITIVE PRESSURE TESTED
MISCELLANEOUS FIRE DOOR
ACCESSORY



SPECIAL NOTES:

- 90-Minute Rated UL Certified Miscellaneous Fire Door Accessory on UL10B and UL10C Wood or Hollow Metal Fire Doors
- To Retain UL Certification, the HP90-MORT must be Installed using GapGuard Fire Caulk