

HP90-MORT

MORTISE HARDWARE PREP FILLER



UL CERTIFIED FOR USE IN
THE US AND CANADA



UL Certified Solution for Fire Doors When Either Removing Existing Hardware and/or Using a New Hardware Type Over Existing Hardware Preps.

PRODUCT INFORMATION

- Application Certified On Both Hollow Metal And Wood Fire-Rated Doors Up To 90 Minutes
- Certified for Filling Mortise Lockset Cavities
- Patented: US Patent US11,959,332 B2

PRODUCT CONSISTS OF:

- + HP90 – 4"×6" Fire-Rated Panel
- + Steel Filler Plates: *(Powder Coated Primer Gray, Embossed With UL Mark)*
 - HP90-MEF1258, Edge Filler Plate
 - HP90-SF4875, Strike Filler Plate
- + Hardware Pack
 - #10-32×1-3/4" FHPH SS Machine Screw
 - #8×3/4" FHPH SS Combo Screw
 - #12×1" FHPH SS Combo Screw
 - #8×3/4" FHPH SS SMS
 - #12×1" FHPH SS SMS
- + GapGuard Fire Caulk
(see Installation Instructions)



POSITIVE PRESSURE TESTED
MISCELLANEOUS FIRE DOOR
ACCESSORY

SPECIAL NOTES:

- 90-Minute Rated UL Certified Miscellaneous Fire Door Accessory on UL10B and UL10C Wood or Hollow Metal Fire Doors
- To Retain UL Certification, the HP90-MORT must be Installed using GapGuard Fire Caulk

Filler
Plate

GapGuard Fire Caulk Fill

HP90

**WOOD DOOR
INSTALLATION
SHOWN**