



712



712-75



732



732-75

**\*NOTE:** These products will require relocation of the center line when used with mortise locks. Consult HES customer support regarding use with the Best 40 series.

**\*\*NOTE:** When using LBMLCM with a 1/2" or 5/8" keeper latchbolt detection may be dependent on the door gap.

# 700 Series

**The industrial grade, fire-rated solution for high abuse applications**

The 700 series is a 3 hour fire-rated, industrial grade electric strike designed for extreme heavy duty applications. The all stainless steel construction of this device makes it ideal for high abuse applications. The 712 series is designed to accommodate 1/2" throw latchbolts, and the 712-75 is designed to accommodate 3/4" latchbolts.\*

## 712

For use with 1/2" to 5/8" throw latchbolts in hollow metal frame applications

*1/2" PK keeper standard*

## 712-75

For use with 1/2\*\*\*, 5/8\*\*\* or 3/4" throw latchbolts in hollow-metal frame applications

*3/4" PK keeper standard*

## 732

For use with 1/2\*\*\* to 5/8\*\*\* throw latchbolts in wood frame applications. Features an offset solenoid

*PK keeper standard*

## 732-75

For use with 1/2", 5/8" or 3/4" throw latchbolts in wood frame applications. Features an offset solenoid

*3/4" PK keeper standard*

## Specifications

- UL 10C fire-rated, 3-hour single door (fail secure only)
- UL 10C fire-rated, 3-hour double door (fail secure only)
- CAN4-S104 (ULC-S104) fire door conformant
- UL 1034, burglary-resistant listed
- UL 294 (6th Edition) listed
- ANSI/BHMA A156.31, Grade 1
- New York City accepted
- NFPA-252 fire door conformant
- ASTM-E152 fire door conformant
- RoHS compliant

## Electrical (continuous duty)

- .29 Amps @ 12VDC
- .15 Amps @ 24VDC
- PoE friendly

## Standard Features

- Tamper-resistant, heavy duty construction
- Constructed entirely of stainless steel for strength and corrosion resistance
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.
- Horizontally adjustable keeper allows for door and frame misalignment
- 1/2" keeper depth (712 and 732)
- 3/4" keeper depth (712-75 and 732-75)
- Non-handed
- Fail Secure (standard)
- Plug-in connector
- Five-year limited warranty

## Optional Features

- Fail Safe
- LBMLCM » Latchbolt & Locking Cam Monitor

## Accessories

- 150 » Strike latch guard
- 152 » Universal mounting tabs
- 2001-1 » Wire-in bridge rectifier
- 2001M » Plug-in bridge rectifier
- 2004M » ElectroLynx® adapter
- 2005M3 » SMART Pac® III
- 2006M » Plug-in buzzer

## Finishes

- 630 » Satin stainless steel
- 605 » Bright brass
- 606 » Satin brass
- 612 » Satin bronze
- 613 » Bronze toned
- 629 » Bright stainless steel

CYLINDRICAL  
LOCKSETSMORTISE LOCKS  
WITHOUT  
DEADBOLTS

GRADE 1



FIRE RATED

UL 1034  
BURGLARY  
LISTED

ASSA ABLOY